POUCH APPLICATORS



POUCH APPLICATOR PA230





Automatic label applicator for bags PA230 is a practical and convenient solution for small and medium-sized manufacturing companies. Compact and easy to operate machine with capacity of 500 to 700 pieces per hour.

The labels need to be placed on a rolin order to start the labeling process. The reading of the labels is performed by a contactles ultrasonic sensor which is produced by us. The bag should be empty so the label can be precisely attached to it via rotating shafts. It has the ability to apply front & back of your pouches.



SPECIFICATIONS:

Supply voltage:	220Vac, 50Hz	D
Own consumption:	< 100VA	S
Electrical connection:	cable with plug type 'SHUKO'	٧
Dimensions:	440mmW, 230mmH, 330mmD	L
Machine weight:	15kg	
Width of the bag:	80 - 250mm	C
Length of the bag:	120 - 350mm	
Thickness of the bag:	< 5mm	t

Diameter of the labels roll:	< 200mm
Spool diameter:	46 - 76mm
Width of the roll / of the label /:	25 - 230mm
Label length:	25 - 300mm
Distance between labels on the tape:	> 2,5mm
Download speed of the tape:	0.03-0.1msec
Distance to start labeling from the edge of the bag:	>25mm

Phone: +971 6 557 99 29 E-mail: multisys@eim.ae Web: www.labelgraff.com W/H: H2 - 006

Sharjah Airport International Free Zone

United Arab Emirates